

DELL EMC NETWORKING TRANSCEIVERS AND CABLES



Features and benefits

- Hot-swappable for simplified maintenance (no power-down required for installation or replacement)
- Some of the smallest and lowest-power 10GbE, 25GbE, 40GbE and 100GbE optical form factors in the industry
- Optical interoperability with SFP, SFP+ and selected QSFP modules
- Offers “pay-as-you-use” model for lower total cost of ownership (TCO) and ease of technology migration
- Reliability ensured by rigorous optics validation, qualification and certification
- Dell EMC product specification encoding feature allows Dell EMC Networking platforms to recognize certified and supported transceivers
- Guaranteed to work with Dell EMC Networking platforms under temperature and process variations with optimal performance

Dell EMC provides optical and cabling options for each Ethernet speed. Long- and short-range optical connectivity options are suited to a wide range of data center and campus applications. For the shortest connections, passive copper direct attach cable (DAC) is a simple and cost-effective solution.

1GbE solutions

1GbE SFP optical transceivers include short-reach (SX), long-reach (LX) and extended long-reach (ZX). A 1000BASE-T transceiver facilitates twisted-pair copper connections.

10GbE solutions

10GbE SFP+ optical transceivers include short-reach-lite (USR), short-reach (SR), long-reach (LR) and extended long-reach (ER and ZR). The 10GbE SFP+ receptacle will also recognize 1GbE SFP transceivers. An LRM transceiver supports links up to 220m over older OM1 and OM2 grade multimode fiber. A 10GBASE-T transceiver facilitates twisted-pair copper connections.

25GbE solutions

25GbE SFP28 optical transceivers include short-reach (SR) and long-reach (LR) variations. In 25GbE networking environments, the 100GbE ports on our Z9100-ON, S6100-ON, S4124-ON and S4148-ON switches can be broken out into four 25GbE lanes by use of either active optical (AOC) or passive copper (DAC) breakout cables.

40GbE solutions

40GbE (4x10GbE) QSFP+ optical transceivers include short-reach (SR4), long-reach (LR4) and extended long-reach (ER4). In many cases, 1GbE SFP and 10GbE SFP+ optics can be readily inserted, recognized, and utilized in the 40GbE QSFP+ receptacle through the use of a (QSA) pluggable adapter. The adapter supports standard SFP and SFP+ optics in a QSFP+ socket providing backwards compatibility, while preserving the 40GbE port for future bandwidth expansion.

40GbE QSFP+ ports support both optical and passive copper (DAC) breakout cables where the four 10GbE lanes are broken out into four individual 10GbE SFP+ interfaces. This solution can be deployed with a single active optical cable (AOC) with integrated QSFP+ and SFP+ transceivers or through the use of a passive fiber breakout cable/multiplexer.

Dell EMC enables cost-savings through the reuse of a legacy 10GbE fiber plant to support new 40GbE connections with our 40GbE duplex (multimode) fiber solutions. These solutions use wavelength multiplexing (SM4) and/or directional multiplexing (BIDI) to transport 40GbE over a single (multimode) fiber pair.

50GbE solutions

50GbE is a relatively new specification utilizing half-populated QSFP28 modules. In 50GbE networking environments, the 100GbE ports on our Z9100-ON, S6100-ON, S4124-ON and S4148-ON switches can be broken out into two pairs of 2x25GbE through a QSFP28 to 2xQSFP28† passive copper direct attach breakout cable (breakout DAC). (The QSFP28† is a half-populated QSFP28 with 2x25GbE lanes.)

100GbE solutions

100GbE (4x25GbE) QSFP28 optical transceivers include short-reach (SR4), intermediate-reach (CWDM4), long-reach (LR4) and extended long-reach (ER4-lite). Standard 10GbE SFP+ and 25GbE SFP28 optics can be readily inserted, recognized, and utilized in the 100GbE QSFP28 receptacle through the use of a (QSA28) pluggable adapter. Although this reduces the effective throughput of the 100GbE port to 25GbE, it provides an immediate low-cost transceiver solution while preserving the option for later bandwidth expansion.

100GbE QSFP28 ports support both optical and passive copper breakout cables. Each of the four 25GbE lanes can be broken out into four individual SFP28 interfaces. This solution can be deployed with a single active optical cable (AOC) with integrated QSFP28 and SFP28 transceivers or through the use of a passive fiber breakout cable/multiplexer.

Testing and warranties

Dell EMC Networking applies a rigorous process in qualifying and maintaining all optics to guarantee a strict adherence to IEEE standards, as well as stringent reliability testing to guarantee a consistent and trustworthy solution.

All optics and cables released by Dell EMC Networking have passed a comprehensive optical analytics check as well as an extensive dynamic test suite. Dell-labeled optics are warrantied alongside the Dell EMC switches in which they are deployed.



SFP+ DAC



QSFP+ DAC



QSFP+ AOC



QSFP+ DAC breakout



SFP SFP+



QSFP+



QSFP+ MPO pigtail



SFP RJ45

DELL EMC TRANSCEIVERS

| Model | Connector type | Wavelength(s) (nm) | Transmission medium | Distance (max.) | Transmitter power (dBm) | Receiver power (dBm) | Power dissipation (max.; W) | Notes |
|---|----------------|--------------------|--|--|-------------------------|----------------------|-----------------------------|--|
| Fast Ethernet (100 Mb/s) SFP transceivers | | | | | | | | |
| SFP-100M-FX | duplex LC | 1310 | MMF FDDI MMF OM1 MMF OM2 MMF OM3 MMF OM4 | 2 km | -15.0 to -20.0 | ≥-30.0 | 1.0 | |
| Gigabit Ethernet SFP transceivers | | | | | | | | |
| SFP-1G-SX | duplex LC | 850 | MMF OM1 MMF OM2 MMF OM3 MMF OM4 | 300 m 500 m 500 m 500 m | -9.0 to -2.5 | ≥-19.0 | 1.0 | |
| SFP-1G-LX | duplex LC | 1310 | SMF | 10 km | -9.5 to -3.0 | ≥-19.0 | 1.0 | |
| SFP-1G-ZX | duplex LC | 1310 | SMF | 80 km | 0.0 to +5.0 | ≥-22.0 | 1.5 | |
| SFP-1G-BX10-U | simplex LC | 1310 | SMF | 10 km | -9.0 to -3.0 | -20.0 to -3.0 | 1.0 | |
| SFP-1G-BX10-D | simplex LC | 1490 | SMF | 10 km | -9.0 to -3.0 | -20.0 to -3.0 | 1.0 | |
| SFP-1G-BX40-U | simplex LC | 1310 | SMF | 40 km | -2.0 to +3.0 | -24.0 to 0.0 | 1.0 | |
| SFP-1G-BX40-D | simplex LC | 1490 | SMF | 40 km | -2.0 to +3.0 | -24.0 to 0.0 | 1.0 | |
| SFP-1G-BX80-U | simplex LC | 1490 | SMF | 80 km | -2.0 to +3.0 | -26.0 to -1.0 | 1.0 | |
| SFP-1G-BX80-D | simplex LC | 1550 | SMF | 80 km | -2.0 to +3.0 | -26.0 to -1.0 | 1.0 | |
| SFP-1G-T | RJ-45 | N/A | CAT5 | 100 m | N/A | N/A | 1.5 | |
| 8G Fibre Channel SFP+ transceivers | | | | | | | | |
| SFP-8GFC-SW | duplex LC | 850 | MMF OM1 MMF OM2 MMF OM3 MMF OM4 | 21 m 50 m 120 m 150 m | -8.2 to -2.0 | ≥-14.2 | 1.0 | |
| SFP-8GFC-LW | duplex LC | 1310 | SMF | 10 km | -8.4 to +0.5 | -13.8 to +0.5 | 1.2 | |
| 10-Gigabit Ethernet SFP+ transceivers | | | | | | | | |
| SFP-10G-USR | duplex LC | 850 | MMF OM1 MMF OM2 MMF OM3 MMF OM4 | 10 m 25 m 100 m 150 m | -5.0 to -1.0 | -9.9 to +0.5 | 1.0 | |
| SFP-10G-SR | duplex LC | 850 | MMF FDDI MMF OM1 MMF OM2 MMF OM3 MMF OM4 | 26 m 33 m 82 m 300 m 400 m | -7.3 to -1.0 | -9.9 to -1.0 | 1.0 | |
| SFP-10G-LRM | duplex LC | 1310 | MMF FDDI MMF OM1 MMF OM2 MMF OM3 MMF OM4 | 220 m | -6.5 to -0.5 | -8.4 to +0.5 | 1.0 | |
| SFP-10G-LR | duplex LC | 1310 | SMF | 10 km | -8.2 to +0.5 | -14.4 to +0.5 | 1.5 | |
| SFP-10G-ER | duplex LC | 1550 | SMF | 40 km | -4.7 to +4.0 | -15.8 to -1.0 | 1.5 | |
| SFP-10G-ZR | duplex LC | 1550 | SMF | 80 km | 0.0 to +4.0 | -24.0 to -7.0 | 1.5 | |
| SFP-10G-DWDM | duplex LC | 1528.7 to 1568.7 | SMF | 80 km | -1.0 to +3.0 | -18.0 to -7.0 | 1.7 | tunable; assumes receiver OSNR > 26 dB |
| SFP-10G-BX10-U* | simplex LC | 1330 | SMF | 10 km | -8.0 to +0.5 | -14.8 to +0.5 | 1.0 | |
| SFP-10G-BX10-D* | simplex LC | 1270 | SMF | 10 km | -8.0 to +0.5 | -14.8 to +0.5 | 1.0 | |
| SFP-10G-BX40-U* | simplex LC | 1330 | SMF | 40 km | 0.0 to +5.0 | -21.2 to -9.0 | 1.5 | |
| SFP-10G-BX40-D* | simplex LC | 1270 | SMF | 40 km | 0.0 to +5.0 | -21.2 to -9.0 | 1.5 | |
| SFP-10G-T | RJ-45 | N/A | CAT6A (10G) CAT5A (1G)* | 30 m 100 m* | N/A | N/A | 2.5 | |

*to be available

All transceivers operate at 0 to 70°C unless otherwise indicated.

Transceivers comply with appropriate standards and MSAs including IEEE 802.3ab, 802.3z, 802.3ae, 802.3ba, 802.3bm and 802.3cc.



DELL EMC TRANSCEIVERS

| Model | Connector type | Wavelength(s) (nm) | Transmission medium | Distance (max.) | Transmitter power (dBm) | Receiver power (dBm) | Power dissipation (max.; W) | Notes |
|---|----------------|------------------------------|---------------------------|------------------------|---|--|-----------------------------|---|
| 16G Fibre Channel SFP+ transceivers | | | | | | | | |
| SFP-16GFC-SW | duplex LC | 850 | MMF OM3 MMF OM4 | 100 m 125 m | -7.8 to 0.0 | -13.5 to 0.0 | 1.0 | |
| SFP-16GFC-LW* | duplex LC | 1310 | SMF | 10 km | -5.0 to 2.0 | -17.0 to +2.0 | 1.2 | |
| Quad 16G Fibre Channel QSFP+ transceivers | | | | | | | | |
| QSFP-64GFC-SW4 | MPO-12 | 850 | MMF OM3 MMF OM4 | 100 m 125 m | -7.8 to 0.0 /lane | -13.5 to 0.0 /lane | 2.5 | compatible with 4 × 16GFC, 4 × 8GFC or 4 × 4GFC |
| 25-Gigabit Ethernet SFP28 transceivers | | | | | | | | |
| SFP-25G-SR | duplex LC | 850 | MMF OM3 MMF OM4 | 70 m 100 m | -9.1 to 0.0 | -11.0 to 0.0 | 1.2 | |
| SFP28-25G-ESR* | duplex LC | 850 | MMF OM3 MMF OM4 | 200 m 300 m | -7.3 to 0.0 | -11.9 to 0.0 | 1.2 | |
| SFP28-25G-LR | duplex LC | 1310 | SMF | 10 km | -7.0 to +2.0 | -13.3 to +2.0 | 1.2 | |
| Quad 32G Fibre Channel QSFP28 transceivers | | | | | | | | |
| Q28-128GFC-SW4 | MPO-12 | 850 | MMF OM3 MMF OM4 | 85 m 100 m | -8.5 to +2.4 /lane | -10.4 to +2.4 /lane | 3.5 | compatible with 4 × 32GFC or 4 × 16GFC |
| 40-Gigabit Ethernet QSFP+ transceivers | | | | | | | | |
| QSFP-40G-SR4 | MPO-12 | 850 | MMF OM3 MMF OM4 | 100 m 150 m | -7.6 to +2.4 /lane | -9.0 to +2.4 /lane | 1.5 | can operate in 1 × 4 breakout mode |
| QSFP-40G-ESR4 | MPO-12 | 850 | MMF OM3 MMF OM4 | 300 m 400 m | -4.3 to -1.0 /lane | -11.1 to -1.0 /lane | 1.5 | can operate in 1 × 4 breakout mode |
| QSFP-40G-LM4 | duplex LC | 1271 1291 1311 1331 | MMF OM3 MMF OM4 SMF | 140 m 160 m 1 km | -7.0 to +4.3 /lane (MMF) -10.0 to +2.3 /lane (SMF) | -10.0 to +4.3 /lane (MMF) -13.7 to +2.3 /lane (SMF) | 3.5 | |
| QSFP-40G-SM4 | duplex LC | 850 880 910 940 | MMF OM3 MMF OM4 | 300 m 300 m | -4.8 to +2.4 /lane | -4.8 to +7.0 /lane | 1.5 | |
| QSFP-40G-BIDI | duplex LC | 850 900 | MMF OM3 MMF OM4 | 100 m 150 m | -4.0 to +5.0 /lane | -10.0 to +5.0 /lane | 3.5 | |
| QSFP-40G-PSM4-LR | MPO-12 | 1310 | SMF | 10 km | -5.5 to +1.5 /lane | 12.6 to +1.5 /lane | 3.5 | can operate in 1 × 4 breakout mode |
| QSFP-40G-LR4 | duplex LC | 1271 1291 1311 1331 | SMF | 10 km | -7.0 to +2.3 /lane | -13.7 to +2.3 /lane | 3.5 | |
| QSFP-40G-ER4 | duplex LC | 1271 1291 1311 1331 | SMF | 40 km | -2.7 to +4.5 /lane | -21.2 to -4.5 /lane | 3.5 | links longer than 30 km are considered engineered links |
| QSA-QSFP-SFP+ | SFP+ | N/A | N/A | N/A | N/A | N/A | N/A | adaptor to use SFP+ modules in QSFP+ receptacles |

* to be available
All transceivers operate at 0 to 70°C unless otherwise indicated.

DELL EMC TRANSCEIVERS

| Model | Connector type | Wavelength(s) (nm) | Transmission medium | Distance (max.) | Transmitter power (dBm) | Receiver power (dBm) | Power dissipation (max.; W) | Notes |
|---|----------------|------------------------------|---------------------|------------------|-------------------------|----------------------|-----------------------------|---|
| 100-Gigabit Ethernet QSFP28 transceivers | | | | | | | | |
| Q28-100G-SR4 | MPO-12 | 850 | MMF OM3 MMF OM4 | 70 m 100 m | -8.4 to +2.4 /lane | -10.3 to +2.4 /lane | 3.5 | can operate in 1 x 4 breakout mode |
| Q28-100G-ESR4* | MPO-12 | 850 | MMF OM3 MMF OM4 | 200 m 300 m | -8.3 to +2.4 /lane | -10.3 to +2.4 /lane | 3.5 | can operate in 1 x 4 breakout mode |
| Q28-100G-SWDM4* | duplex LC | 850 880 910 940 | MMF OM3 MMF OM4 | 75 m 100 m | -7.6 to +3.4 /lane | -10.1 to +3.4 /lane | 3.5 | |
| Q28-100G-PSM4-IR | MPO-12 | 1310 | SMF | 2 km | -5.5 to +2.0 /lane | -10.2 to +2.0 /lane | 3.5 | can operate in 1 x 4 breakout mode |
| Q28-100G-CWDM4 | duplex LC | 1271 1291 1311 1331 | SMF | 2 km | -6.5 to +2.5 /lane | -11.5 to +2.5 /lane | 3.5 | |
| Q28-100G-LR4 | duplex LC | 1296 1300 1305 1309 | SMF | 10 km | -4.3 to +4.5 /lane | -10.6 to +4.5 /lane | 3.5 | |
| Q28-100G-ER4-lite* | duplex LC | 1296 1300 1305 1309 | SMF | 35 km (with FEC) | -1.9 to +4.5 /lane | -17.7 to -4.6 /lane | 5.0 | specifications for use with FEC, max. distance is 30 km without FEC |
| QSA-Q28-S28* | | N/A | N/A | N/A | N/A | N/A | N/A | adaptor to use SFP28 modules in QSFP28 receptacles |
| 100-Gigabit Ethernet CXP transceivers | | | | | | | | |
| CXP-100G-SR10 | MPO-24 | 850 | MMF OM3 MMF OM4 | 100 m 150 m | -7.6 to +2.4 /lane | -9.5 to +2.4 /lane | 3.0 | |

*to be available
All transceivers operate at 0 to 70°C unless otherwise indicated.

DELL EMC ACTIVE OPTICAL CABLES (AOC) AND DIRECT ATTACH CABLES (DAC)

| Model | Available lengths (m) | Connection | Transmission medium | Power dissipation per end (max.; W) | Notes |
|--|------------------------|-----------------------|---------------------|-------------------------------------|------------------------------------|
| 10-Gigabit Ethernet Active Optical and Direct Attach Cable | | | | | |
| DAC-SFP-10G-xM | 0.5, 1, 2, 3, 5, 7 | SFP+ to SFP+ | copper | | |
| AOC-SFP-10G-xM | 2, 3, 5, 7, 10, 15, 20 | SFP+ to SFP+ | optical | 1.5 | |
| 25-Gigabit Ethernet Active Optical and Direct Attach Cable | | | | | |
| DAC-SFP-25G-xM* | 1, 2, 3, 5 | SFP28 to SFP28 | copper | | 1, 2, 3 m can operate without FEC |
| AOC-SFP-25G-xM* | 7, 10, 15, 20 | SFP28 to SFP28 | optical | 1.5 | operates with FEC |
| 40-Gigabit Ethernet Active Optical and Direct Attach Cable | | | | | |
| DAC-QSFP-40G-xM | 0.5, 1, 2, 3, 5, 7 | QSFP+ to QSFP+ | copper | | |
| AOC-QSFP-40G-xM | 3, 10, 50 | QSFP+ to QSFP+ | optical | 1.5 | |
| DAC-QSFP-4SFP-10G-xM | 0.5, 1, 2, 3, 5, 7 | QSFP+ to 4 × SFP+ | copper | | |
| AOC-QSFP-4SFP-10G-xM | 10, 30 | QSFP+ to 4 × SFP+ | optical | 1.5 | supports 4×10G or 4×1G |
| DAC-QSFP-4RJ45-1G-1M | 1 | QSFP+ to 4 × RJ-45 | copper | 1.5 | active copper |
| 100-Gigabit Ethernet Active Optical and Direct Attach Cable | | | | | |
| DAC-QSFP-100G-xM | 1, 2, 3, 5 | QSFP28 to QSFP28 | copper | | 1, 2, 3 m can operate without FEC |
| AOC-QSFP-100G-xM | 3, 7, 10, 30, 50 | QSFP28 to QSFP28 | optical | 3.5 | operates with FEC |
| DAC-QSFP-2QSFP28-50G-xM | 1, 2, 3 | QSFP28 to 2 × QSFP28† | copper | | QSFP28t modules are half-populated |
| DAC-QSFP-4SFP28-25G-xM | 1, 2, 3 | QSFP28 to 4 × SFP28 | copper | | 1, 2, 3 m can operate without FEC |
| AOC-QSFP-4SFP28-25G-xM* | 10, 15, 30 | QSFP28 to 4 × SFP28 | optical | 3.5 | operates with FEC |

DELL EMC PASSIVE OPTICAL CABLES

| Model | Available lengths (m) | Connection | Transmission medium | Notes |
|-------------------------------|---------------------------------|------------------------|---------------------|-------|
| Passive optical cables | | | | |
| CBL-MPO12-OM4-xM | 1, 3, 5, 7, 10, 25, 50, 75, 100 | MPO-12 to MPO-12 | MMF OM4 | |
| CBL-LC-OM4-xM* | 1, 2, 3, 5, 10, 30, 50, 100 | LC to LC | MMF OM4 | |
| CBL-MPO12-4LC-OM4-xM | 1, 3, 5, 7 | MPO-12 to 4 × LC | MMF OM4 | |
| CBL-MPO12-4LC-SMF-5M | 5 | MPO-12 to 4 × LC | SMF | |
| CBL-MPO24-OM4-5M | 5 | MPO-24 to MPO-24 | MMF OM4 | |
| Breakout boxes | | | | |
| 64x breakout box-OM4 | 1.5 | 16 × MPO-12 to 64 × LC | MMF OM4 | |
| 64x breakout box-SMF | 1.5 | 16 × MPO-12 to 64 × LC | SMF | |
| 48x breakout box-OM4 | 1.5 | 12 × MPO-12 to 48 × LC | MMF OM4 | |

PRODUCT SUPPORT *

| 10-GbE transceivers | SFP-10G-USR | SFP-10G-SR | SFP-10G-LR | SFP-10G-LRM | SFP-10G-ER | SFP-10G-ZR | SFP-10G-T-DWDM | SFP-10G-T10 |
|--|-------------|------------|------------|-------------|------------|------------|----------------|-------------|
| Z9100-ON | ✓ | ✓ | ✓ | | ✓ | ✓ | ✓ | ✓ |
| S6100-ON | ✓ | ✓ | ✓ | | ✓ | ✓ | ✓ | ✓ |
| S6010-ON | | ✓ | ✓ | | ✓ | ✓ | ✓ | ✓ |
| S5000 | | ✓ | ✓ | | ✓ | ✓ | ✓ | ✓ |
| S4048T | | ✓ | ✓ | | ✓ | ✓ | ✓ | ✓ |
| S4128-ON / S4148-ON | ✓ | ✓ | ✓ | ✓*** | ✓ | ✓ | | |
| S4048 / S4048-ON | | ✓ | ✓ | | ✓ | ✓ | ✓ | ✓** |
| N4000 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | |
| X4012 | ✓ | ✓ | ✓ | | ✓ | ✓ | | |
| N2128-ON | ✓ | ✓ | ✓ | | ✓ | ✓ | | |
| N3132-ON | ✓ | ✓ | ✓ | | ✓ | ✓ | | |
| S31XX | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | |
| S5048 | ✓* | ✓* | | | ✓* | ✓* | ✓* | ✓** |
| S5148 | ✓* | ✓* | | | ✓* | ✓* | ✓* | ✓** |
| N20XX / N30XX | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | |
| S3048-ON | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | |
| X1052 | ✓ | ✓ | ✓ | | ✓ | | | |
| MXL & IO Agg | ✓ | ✓ | ✓ | ✓ | ✓ | | | |
| VRTX IOA & MXL | ✓ | ✓ | | | | | | |
| FN IOM pass-through | ✓ | ✓ | ✓ | ✓ | | | ✓ | |
| M8024-K | ✓ | ✓ | ✓ | ✓ | | | | |
| M6220 | ✓ | ✓ | ✓ | ✓ | | | | |
| M6348 | ✓ | ✓ | ✓ | ✓ | | | | |
| 10Gb Pass-thru-K | ✓ | ✓ | | | | | | |
| C-Series 36pt 1000BASE-T (and PoE) Comb Line Card: 2 10Gb SFP+ ports | | ✓ | ✓ | | ✓ | | | |
| C-Series 8 pt 10Gb SFP+ Line Card | | ✓ | ✓ | ✓ | ✓ | | | |
| C9010 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | |

* supported in upcoming software release

** population of SFP-10G-T transceivers in switch may be limited due to power constraints.

*** only supported on S4148FE

PRODUCT SUPPORT*

| | 40 GbE transceivers | QSFP-40G-SR4 | QSFP-40G-ESR4 | QSFP-40G-LR4 | QSFP-40G-PSM4-LR | QSFP-40G-LM4 | QSA-QSFP-SFP+ | QSFP-40G-SM4 | QSFP-40G-BIDI |
|-----------------------------------|--|--------------|---------------|--------------|------------------|--------------|----------------|--------------|---------------|
| TOR switches | Z9100-ON | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓* |
| | S6100-ON | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓* |
| | S6010-ON | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓* |
| | S5000 | ✓ | ✗ | ✓ | | ✓ | ✓ | ✓ | ✓* |
| | S40T48 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓* |
| | S4810/S4810-ON | ✓ | ✓ | ✓ | ✓ | | | ✓ | ✓* |
| | S4124-ON/S4148-ON | ✓ | ✓ | ✓ | ✓ | ✓ | ✓* | ✓ | |
| | S4048/S4048-ON | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓* |
| | 8100/N4000 | ✓ | ✓ | ✓ | | | | ✓* | |
| | N3132-ON | ✓ | ✓ | ✓ | | | | | |
| | S5048 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓* |
| | S5148 | ✓* | ✓* | ✓* | ✓* | ✓* | ✓* | ✓* | ✓* |
| 1GbE TOR | X4012 | | | | | | Not applicable | | |
| | N20XX / N30XX, S3048 / S3048-ON, 35XX, 28XX, X10XX, X1052 | | | | | | Not applicable | | |
| M100e, VRTX and FN blade switches | MXL & IO Agg | ✓ | ✓ | | | | | ✓ | |
| | VRTX IOA & MXL | | | | | | Not applicable | | |
| | FN IOM pass-through | | | | | | Not applicable | | |
| | M8024-K | | | | | | Not applicable | | |
| | M6220 | | | | | | Not applicable | | |
| | M6348 | | | | | | Not applicable | | |
| | 10Gb Pass-thru-K | | | | | | Not applicable | | |
| | M8428-K | | | | | | Not applicable | | |
| C-Series Line Cards | C-Series 48pt 1000Base-T Line Card | | | | | | Not applicable | | |
| | C-Series 48pt 1000Base-T PoE Line | | | | | | Not applicable | | |
| | C-Series 48pt 1Gb SFP Line Card | | | | | | Not applicable | | |
| | C-Series 36pt 1000BASE-T (and PoE) Comb Line Card: 2 10Gb SFP+ ports | | | | | | Not applicable | | |
| | C-Series 36pt 1000BASE-T (and PoE) Comb Line Card: 8pt 1Gb SFP | | | | | | Not applicable | | |
| | C-Series 4 pt 10Gb XFP Line Card | | | | | | Not applicable | | |
| | C-Series 8 pt 10Gb XFP Line Card | | | | | | Not applicable | | |
| | C-Series 8 pt 10Gb SFP+ Line Card | | | | | | Not applicable | | |
| | C-Series Line Card QSFP+ ports | ✓ | ✓ | | | | | | |
| | C9010 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | |

*Supported in upcoming software release

PRODUCT SUPPORT

| 100GbE transceivers | Q28-100G-SR4 | Q28-100G-LR4 | Q28-100G-PSM4-IR | CXP-100G-SR10 | Q28-100G-CWDM4 | Q28-100G-SWDM4 | QSA-Q28-S28 | Q28-100G-ER4-lite | Q28-100G-ESR4 |
|---------------------|--------------|--------------|------------------|---------------|----------------|----------------|-------------|-------------------|---------------|
| Z9100-ON | ✓ | ✓ | ✓ | | ✓ | ✓* | ✓* | ✓* | ✓* |
| S6100-ON | ✓ | ✓ | ✓ | ✓ | ✓ | ✓* | ✓* | ✓* | ✓* |
| S4124-ON/S4148-ON | ✓ | ✓ | ✓ | | ✓ | ✓* | ✓* | | |

| 25GbE transceivers | SFP28-25G-SR | SFP28 -25G-ESR | SFP28-25G-LR |
|---------------------|--------------|----------------|--------------|
| S4124-ON / S4148-ON | ✓ | ✓* | ✓ |
| Z9100-ON | ✓ | ✓* | ✓ |
| S6100-ON | | | ✓ |

ORDERING INFORMATION

| Model | Product description |
|--|---|
| Fast Ethernet (100 Mb/s) SFP transceivers | |
| SFP-100M-FX | 100MbE SFP optical module, up to 2 km over 2 parallel MMFs |
| Gigabit Ethernet SFP transceivers | |
| SFP-1G-SX | 1GbE SFP optical module, short-reach, up to 500 m over 2 parallel MMFs |
| SFP-1G-LX | 1GbE SFP optical module, long-reach, up to 10 km over 2 parallel SMFs |
| SFP-1G-ZX | 1GbE SFP optical module, extended-reach, up to 80 km over 2 parallel SMFs |
| SFP-1G-BX10-U | 1GbE SFP optical module, bi-directional, long-reach, up to 10 km over single SMF - U version |
| SFP-1G-BX10-D | 1GbE SFP optical module, bi-directional, long-reach, up to 10 km over single SMF - D version |
| SFP-1G-BX40-U | 1GbE SFP optical module, bi-directional, extended-reach, up to 40 km over single SMF - U version |
| SFP-1G-BX40-D | 1GbE SFP optical module, bi-directional, extended-reach, up to 40 km over single SMF - D version |
| SFP-1G-BX80-U | 1GbE SFP optical module, bi-directional, extended-reach, up to 80 km over single SMF - U version |
| SFP-1G-BX80-D | 1GbE SFP optical module, bi-directional, extended-reach, up to 80 km over single SMF - D version |
| SFP-1G-T | 1GbE SFP electrical 1000BASE-T module, up to 100 m over single CAT5 cable. |
| 8G Fibre Channel SFP+ transceivers | |
| SFP-8GFC-SW | 8GFC SFP+ optical module, short-reach, up to 150 m over 2 parallel MMFs |
| SFP-8GFC-LW | 8GFC SFP+ optical module, long-reach, up to 10 km over 2 parallel SMFs |
| 10-Gigabit Ethernet SFP+ transceivers | |
| SFP-10G-USR | 10GbE SFP+ optical module, ultra-short-reach, up to 150 m over 2 parallel MMFs |
| SFP-10G-SR | 10GbE SFP+ optical module, short-reach, up to 400 m over 2 parallel MMFs |
| SFP-10G-SR-12 | 10GbE SFP+ optical module, short-reach, up to 400 m over 2 parallel MMFs, package of 12 |
| SFP-10G-LRM | 10GbE SFP+ optical module, long-reach multi-mode, up to 220 m over 2 parallel FDDI, OM1 or OM2 MMFs |
| SFP-10G-LR | 10GbE SFP+ optical module, long-reach, up to 10 km over 2 parallel SMFs |
| SFP-10G-ER | 10GbE SFP+ optical module, extended-reach, up to 40 km over 2 parallel SMFs |
| SFP-10G-ZR | 10GbE SFP+ optical module, extended-reach, up to 80 km over 2 parallel SMFs |
| SFP-10G-DWDM | 10GbE SFP+ optical module, tunable DWDM, extended-reach, up to 80 km over 2 parallel SMFs |
| SFP-10G-BX10-U* | 10GbE SFP+ optical module, bi-directional, long-reach, up to 10 km over single SMF - U version |
| SFP-10G-BX10-D* | 10GbE SFP+ optical module, bi-directional, long-reach, up to 10 km over single SMF - D version |
| SFP-10G-BX40-U* | 10GbE SFP+ optical module, bi-directional, extended-reach, up to 40 km over single SMF - U version |
| SFP-10G-BX40-D* | 10GbE SFP+ optical module, bi-directional, extended-reach, up to 40 km over single SMF - D version |
| SFP-10G-T | 10GbE SFP+ electrical 10GBASE-T module, up to 30 m over single CAT6A cable |

ORDERING INFORMATION

| Model | Product description |
|---|---|
| 16G Fibre Channel SFP+ transceivers | |
| SFP-16GFC-SW | 16GFC SFP+ optical module, short-reach, up to 125 m over 2 parallel MMFs |
| SFP-16GFC-LW | 16GFC SFP+ optical module, long-reach, up to 10 km over 2 parallel SMFs |
| Quad 16G Fibre Channel QSFP+ transceivers | |
| QSFP-64GFC-SW4 | Quad 16GFC QSFP+ optical module, short-reach, up to 100 m over 8 parallel MMFs |
| 25-Gigabit Ethernet SFP28 transceivers | |
| SFP-25G-SR | 25GbE SFP28 optical module, short-reach, up to 100 m over 2 parallel MMFs |
| SFP-25G-SR-NOF* | 25GbE SFP28 optical module, short-reach, FEC-free operation up to 40 m over 2 parallel MMFs |
| Quad 32G Fibre Channel QSFP28 transceivers | |
| Q28-128GFC-SW4 | Quad 32GFC QSFP28 optical module, short-reach, up to 1xx m over 8 parallel MMFs |
| 40-Gigabit Ethernet QSFP+ transceivers | |
| SFP-40G-SR4 | 40GbE QSFP+ optical module, short-reach, up to 150 m over 8 parallel MMFs |
| QSFP-40G-ESR4 | 40GbE QSFP+ optical module, extended short-reach, up to 400 m over 8 parallel MMFs |
| QSFP-40G-LM4 | 40GbE QSFP+ optical module, WDM, short-reach, up to 160 m over 2 parallel MMFs |
| QSFP-40G-SM4 | 40GbE QSFP+ optical module, SWDM, short-reach, up to 300 m over 2 parallel MMFs |
| QSFP-40G-BIDI | 40GbE QSFP+ optical module, bi-directional, short-reach, up to 160 m over 2 parallel MMFs |
| QSFP-40G-PSM4-LR | 40GbE QSFP+ optical module, long-reach, up to 10 km over 8 parallel SMFs |
| QSFP-40G-LR4 | 40GbE QSFP+ optical module, long-reach, up to 10 km over 2 parallel SMFs |
| QSFP-40G-ER4 | 40GbE QSFP+ optical module, extended-reach, up to 40 km over 2 parallel SMFs |
| QSA-QSFP-SFP | 40GbE QSFP+ to 10GbE SFP+ adapter |
| 100-Gigabit Ethernet QSFP28 transceivers | |
| Q28-100G-SR4 | 100GbE QSFP28 optical module, short-reach, up to 100 m over 8 parallel MMFs |
| Q28-100G-ESR4* | 100GbE QSFP28 optical module, extended short-reach, up to 300 m over 8 parallel MMFs |
| Q28-100G-SWDM4* | 100GbE QSFP28 optical module, SWDM, short-reach, up to 100 m over 2 parallel MMFs |
| Q28-100G-PSM4-IR | 100GbE QSFP28 optical module, intermediate-reach, up to 2 km over 8 parallel SMFs |
| Q28-100G-CWDM4 | 100GbE QSFP28 optical module, intermediate-reach, up to 2 km over 2 parallel SMFs |
| Q28-100G-LR4 | 100GbE QSFP28 optical module, long-reach, up to 10 km over 2 parallel SMFs |
| Q28-100G-ER4-lite* | 100GbE QSFP28 optical module, extended-reach, up to 35 km over 2 parallel SMFs |
| QSA-Q28-S28* | 100GbE QSFP28 to 25GbE SFP28 adapter |
| 100-Gigabit Ethernet CXP transceivers | |
| CXP-100G-SR10 | 100GbE CXP optical module, short-reach, up to 150 m over 20 parallel MMFs |

Learn More at Dell.com/Networking

© 2017 Dell Inc. All rights reserved. Dell Networks, E-Series are registered trademarks and, C-Series, Dell Networking OS9, Z-Series and S-Series, are trademarks of Dell, Inc. All other company names are trademarks of their respective holders. Information in this document is subject to change without notice. Dell Inc. assumes no responsibility for any errors that may appear in this document.